

SONANCE

ESTABLISHED 1983



## OUTDOOR SYSTEMS



### SONANCE LANDSCAPE SERIES

- Ultimate Outdoor Audio Designed for Even Balanced Coverage
- Flexible Mix and Match Design Options
- Sonance Hi Fidelity Laminated Core Transformer with Multiple Tap Settings
- 70V/100V or 8 Ohm Across All Models



### SONANCE GARDEN SERIES

- Balance of Performance and Simplicity
- 8.1 System, up to 16.2 Configurations
- Up to 300 Sq. Meters
- Pivoting Knuckle for Precise Audio Direction
- Removable 9" Ground Stakes Included



### SONARRAY

- Simplicity and Value for Even, Balanced Coverage up to 232 Sq. Meters
- 8 1 System, up to 16.2 Configurations

SONARRAY

# LANDSCAPE SERIES

	SLS SATS LS4T/LS6T	SLS SUBS LS12T & HS12T/LS15T
<b>Tweeter:</b>	25mm Polyurethane dome	-
<b>Woofers:</b>	114mm/165mm polypropylene cone with a Santoprene rubber surround	305mm/381mm polypropylene cone with a Santoprene rubber surround
<b>Frequency Response:</b>	75Hz - 20kHz +/-3dB/ 55Hz - 20kHz +/-3dB	22Hz - 100Hz +/-3dB/ 20Hz - 100Hz +/-3dB
<b>Taps:</b>	60W, 30W, 15W, (7.5W 70V), 8 Ohms	300W, 150W, 75W, (38W 70V), 8 Ohms

# GARDEN SERIES

	SGS SAT	SGS SUB
<b>Tweeter:</b>	19mm Polyurethane dome	-
<b>Woofers:</b>	98mm anodized aluminum cone & Santoprene surround	254mm dual voice coil, polypropylene & Santoprene surround
<b>Frequency Response:</b>	80Hz - 20kHz +/-3dB	35Hz - 100Hz +/-3dB
<b>Sensitivity:</b>	87dB 2.83V / 1 meter	90dB 2.83V / 1 meter

# SONARRAY

	SRI SAT	SRI SUB
<b>Woofers:</b>	98mm anodized aluminum cone & Santoprene surround	203mm dual voice coil, polypropylene & Santoprene surround
<b>Frequency Response:</b>	40Hz-20kHz +/-3dB	45Hz - 100Hz +/-3dB
<b>Sensitivity:</b>	85dB 2.83V / 1 meter	89dB 2.83V / 1 meter